
Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-420-5236

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 3b 1st end |
| Inside Diameter: |
| 0.380 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.840 inches |
| Minimum Inside Bending Radius: |
| 5.000 inches |
| Quick Disconnect Size: |
| 1.080 inches 2nd end |
| End Application: |
| 2350-01-390-4683 |
| Connection Style: |
| Push (internal) 1st end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Internal quick disconnect 1st end |
| Burst Test Pressure: |
| 16000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 4300.0 pounds per square inch |
| Hydrostatic Test Pressure: |
| 8000.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 144.000 inches |
| Special Features: |
| Both ends have a quick disconect |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 4720-01-420-5236

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

