NSN 4720-01-420-8042

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-420-8042

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.190 inches
Tempurature Rating:
-25.0 degrees fahrenheit single response and 125.0 degrees fahrenheit single response
Outside Diameter:
0.520 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Black
Hose Or Tubing Specification/std Data:
Sae j517, 100r5, type a-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Second End Relationship With First End:
Identical
Burst Test Pressure:
12000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer braided steel wire err-100
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end

37.0 degrees 1st end

Seat Angle:

NSN 4720-01-420-8042

Nonmetallic Hose Assembly - Page 2 of 2



Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
30.000 inches
Thread Series Designator:
Unf 1st end
Specification Data:
Sae j517, 100r5, type a-81343 national std/spec
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0