

View Online at <https://aerobasegroup.com/nsn/4720-01-421-0118>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.750 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 190.0 degrees fahrenheit single response

**Outside Diameter:**

1.095 inches

**Minimum Inside Bending Radius:**

2.750 inches

**End Application:**

Aircraft airlifter c-17a

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 1st end

**Burst Test Pressure:**

500.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire and outer layer woven polyamide cord

**Maximum Operating Pressure:**

125.0 pounds per square inch

**Thread Size:**

1.062 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

250.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fire resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

42.000 inches working

**Special Features:**

Nut color blue; used in airborne potable water system

**Thread Series Designator:**

Unj 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0