NSN 4720-01-421-1549

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-421-1549

3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.188 inches and 0.214 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
Outside Diameter:
Between 0.472 inches and 0.510 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel 2nd end
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Not identical
Burst Test Pressure:
6000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
15.000 inches working

NSN 4720-01-421-1549

Nonmetallic Hose Assembly - Page 2 of 2



Second End Swivel Action Capability: Not included Special Features: Inner conveying tube material-rubber, buna-n Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 2nd end Shelf Life: N/a Unit Of Measure: - Demilitarization:

No

Fiig:

A542a0