NSN 4720-01-421-3476

Cross Sectional Shape:

15.000 inches working

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-421-3476

3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.602 inches				
Tempurature Rating:				
-54.0 degrees celsius single response and 204.0 degrees celsius single response				
Outside Diameter:				
0.884 inches				
Minimum Inside Bending Radius:				
3.875 inches				
End Application:				
Ea6/ab-dcn				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Thready Qty Per Inch (tpi):				
12 1st end				
Burst Test Pressure:				
12000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer braided corrosion resistant steel wire				
Maximum Operating Pressure:				
3000.0 pounds per square inch				
Thread Size:				
1.0625 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
6000.0 pounds per square inch				
Outer Covering Environmental Protection:				
Corrosion resistant				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				

NSN 4720-01-421-3476

Nonmetallic Hose Assembly - Page 2 of 2



	laa a al	C!	D!	_4
ı	nread	Series	Design	ator:

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0