Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-421-8137

Cross Sectional Shape: Round Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating: -50.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.530 inches Minimum Inside Bending Radius: 2.000 inches End Application: 1740-01-253-8064; support equipment c-17a aircraft Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostati Test Pressure:
Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating: -50.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.530 inches Minimum Inside Bending Radius: 2.000 inches End Application: 1740-01-253-8064; support equipment c-17a aircraft Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Gty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Ender Size: 0.087 inches 1st end
2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating: -50.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.530 inches Minimun Inside Bending Radius: 2.000 inches End Application: 1740-01-253-8064; support equipment c-17a aircraft Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size 0.687 inches 1st end
Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating: -50.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.530 inches Minimum Inside Bending Radius: 2.000 inches End Application: 1740-01-253-8064; support equipment c-17a aircraft Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided stel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end
Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating: -50.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.530 inches Minimum Inside Bending Radius: 2.000 inches End Application: 1740-01-253-8064; support equipment c-17a aircraft Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end
Inside Diameter: 0.250 inches Tempurature Rating: -50.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.530 inches Minimum Inside Bending Radius: 2.000 inches End Application: 1740-01-253-8064; support equipment c-17a aircraft Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end
0.250 inches Tempurature Rating: -50.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.530 inches Minimum Inside Bending Radius: 2.000 inches End Application: 1740-01-253-8064; support equipment c-17a aircraft Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
Tempurature Rating: -50.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.530 inches Minimum Inside Bending Radius: 2.000 inches End Application: 1740-01-253-8064; support equipment c-17a aircraft Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Oty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end
-50.0 degrees fahrenheit and 212.0 degrees fahrenheit single responseOutside Diameter:0.530 inchesMinimun Inside Bending Radius:2.000 inchesEnd Application:1740-01-253-8064; support equipment c-17a aircraftConnection Style:Swivel nut, gasket seal 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endThready Gty Per Inch (tpi):16 1st endBurst Test Pressure:12000.0 pounds per square inchLayer Composition And Location:1st layer braided steel wire and outer layer woven polyamide cordMaximum Operating Pressure:3000.0 pounds per square inchThread Size:0.687 inches 1st endHydrostatic Test Pressure:
Outside Diameter: 0.530 inches Minimum Inside Bending Radius: 2.000 inches End Application: 1740-01-253-8064; support equipment c-17a aircraft Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Layer Composition And Location: 0.687 inches 1st end
0.530 inches Minimum Inside Bending Radius: 2.000 inches End Application: 1740-01-253-8064; support equipment c-17a aircraft Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
Minimum Inside Bending Radius: 2.000 inches End Application: 1740-01-253-8064; support equipment c-17a aircraft Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
2.000 inches End Application: 1740-01-253-8064; support equipment c-17a aircraft Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end
End Application: 1740-01-253-8064; support equipment c-17a aircraft Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
1740-01-253-8064; support equipment c-17a aircraft Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end
Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end
Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
Thready Qty Per Inch (tpi): 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
 16 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
12000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
Layer Composition And Location: 1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
1st layer braided steel wire and outer layer woven polyamide cord Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
3000.0 pounds per square inch Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
Thread Size: 0.687 inches 1st end Hydrostatic Test Pressure:
0.687 inches 1st end Hydrostatic Test Pressure:
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant
Inside Surface Condition:
inside Suitade Condition.
Smooth
Smooth
Smooth Measuring Method And Length:

Nonmetallic Hose Assembly - Page 2 of 2

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

