

View Online at <https://aerobasegroup.com/nsn/4720-01-421-8140>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Outside Diameter:

0.530 inches

Minimum Inside Bending Radius:

2.000 inches

End Application:

1740-01-253-8064; support equipment c-17a

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

16 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and outer layer woven polyamide cord

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.687 inches 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

34.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon and air and water single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0