NSN 4720-01-421-8794

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-421-8794

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.343 inches
Minimum Inside Bending Radius:
2.000 inches
End Application:
Support equipment, c-17a aircraft
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nuts drilled for lockwire
Thready Qty Per Inch (tpi):
16 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
Thread Size: 0.438 inches 1st end
0.438 inches 1st end
0.438 inches 1st end Seat Angle:
0.438 inches 1st end Seat Angle: 37.0 degrees 1st end
0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure:
0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch
0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition:

NSN 4720-01-421-8794

Nonmetallic Hose Assembly - Page 2 of 2



Special	Features:
---------	-----------

Shipping closures required; 2642-9 sleeve 1 in. Long over identification band

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0