NSN 4720-01-421-8803

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-421-8803

Cross Sectional Shape:					
Round					
Thread Class:					
3b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.250 inches					
Tempurature Rating:					
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response					
Outside Diameter:					
0.470 inches					
Minimum Inside Bending Radius:					
2.000 inches					
Exterior Color:					
Black					
End Application:					
4940-01-385-1794; support equipment, c-17a aircraft					
Connection Style:					
Swivel nut flare 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Burst Test Pressure:					
12000.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided steel wire and outer layer molded rubber, synthetic					
Maximum Operating Pressure:					
3000.0 pounds per square inch					
Thread Size:					
0.438 inches 1st end					
Seat Angle:					
37.0 degrees 1st end					
Hydrostatic Test Pressure:					
6000.0 pounds per square inch					
Outer Covering Environmental Protection:					
Abrasion resistant and weatherproof					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					

312.000 inches

NSN 4720-01-421-8803

Nonmetallic Hose Assembly - Page 2 of 2



Th		Carias	Dania	
111	ıeau	Series	Desid	mator.

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0