Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-421-8808

Cross Sectorial Graps: Shound Thread Class: 3b 1st end Thread Direction: Righ-hand 1st end Inside Diameter: 0.500 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Minimu Inside Bending Radius: 5.500 inches Pind Application: Support equipment, c-17a and f-17 aircraft Connection Style: Switel nut flare 2nd end End Connection Design: Straight 2nd end Connection Style: Nuts drilled for lockwire Threaded internal tube 1st end Features Provided: Nuts drilled for lockwire Threaded internal tube 1st end Eust Test Pressure: 000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1.062 inches 2nd end Sect Angle: 3.7.0 degrees 2nd end Hydrostatic Test Pressure: <t< th=""><th>Cross Sectional Shape:</th></t<>	Cross Sectional Shape:
Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.500 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Minimum Inside Bending Radius: 5.50 diptes End Application: Support equipment, c-17a and f-17 aircraft Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Thready dry Per Inch (tpi): 12 2nd end Eust Test Pressure: 1300.0 pounds per square inch Layer Composition And Location: 1000.0 pounds per square inch Maximum Operating Pressure: 1500.0 pounds per square inch Maximum Operating Pressure: 1500.0 geneds 2nd end Straight 2nd end Burst Test Pressure: 1500.0 gounds per square inch Layer Composition And Location: 1500.0 gounds per square inch Straight 2nd end <t< td=""><td></td></t<>	
3b 1 st end Thread Direction: Right-hand 1 st end Inside Diameter: 0.500 inches Temparture Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Minimun Inside Bending Radius: 5.500 inches End Application: Support equipment, c-17a and f-17 aircraft Connection Style: Sivial nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Features Provided: Nuts drilled for lockwire Thready Oty Per Inch (tpi): 12 drand Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Sto0.0 pounds per square inch Hardial Concelion Signe: 1.00.0 pounds per square inch Stola change: 1.01.0 counds per square inch Hardies Condition: 1.020 inches 2nd end Store for Stola change: 1.020 inches 2nd end	
Thread Direction: Right-hand 1st end Right-hand 1st end Inside Diameter: 0.500 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Minimun Inside Bending Radius: 5.500 inches End Application: 5.500 inches End Application: Support equipment, c-17a and f-17 aircraft Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Features Provided: Nuts drilled for lockwire Thready Gty Per Inch (tpi): 12 2nd end Burst Test Pressure: 1000.0 pounds per square inch Azimum Operating Pressure: 1.062 inches 2nd end Set Angle: 3.7.0 degrees 2nd end Hydrosatic Test Pressure: 3.00.0 pounds per square inch India Surface Condition: Suport Support Supp	
Right-hand 1st end Inside Diameter: 0.500 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Minimun Inside Bending Radius: 5.500 inches End Application: Support equipment, c-17a and f-17 aircraft Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Features Provided: Nuts drilled for lockwire Thready Oty Per Inch (tpi): 12 2nd end Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1.062 inches 2nd end Hydrosatic Test Pressure: 1.06	
Inside Diameter: 0.500 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Minmun Inside Bending Radius: 5.500 inches End Application: Support equipment, c-17a and f-17 aircraft Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Features Provided: Nuts drilled for lockwire Thready Oty Per Inch (tpl): 12 2nd end Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1.060.0 pounds per square inch Thread Size: 1.020 cliches 2nd end Hydrosatic Test Pressure: 1.020.0 pounds per square inch Hydrosatic Test Pressure: 1.020.0 pounds per square inch Hydrosatic Test Pressure: 1.020.0 pounds per square inch	
0.500 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Minimum Inside Bending Radius: 5.500 inches End Application: Support equipment, c-17a and f-17 aircraft Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded Internal tube 1st end Features Provided: Nuts drilled for lockwire Threaded Internal tube 1st end Features Provided: Nuts drilled for lockwire Threade Juster Provided: Nuts drilled for lockwire Threade Juster Provide: Nuts drilled for lockwire Support Provide: Nuts drilled for lockwire Support Provide: Nuts drilled for lockwire Support Provide: Nuts drilled for lockwire Support Provide: Nuts drilled for lockwire Nuts drilled for lockwire Nuts dri	-
Tempurture Rating: -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Minimum Inside Bending Radius: 5.500 inches End Application: Support equipment, c-17a and f-17 aircraft Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Features Provided: Nuts drilled for lockwire Thready Oty Per Inch (tpi): 12 2nd end Burst Test Pressure: 700.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1002.0 pounds per square inch Thread Size: 1.062 inches 2nd end Set Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 300.0 pounds per square inch Inside Surface Condition: Source Surface Condition: Source Surface Condition: Sitte Stat Surface Condition: Sitte Surface Cond	
-6.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Minimum Inside Bending Radius: 5.500 inches End Application: Support equipment, c-17a and f-17 aircraft Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Features Provided: Nuts drilled for lockwire Thready Oty Per Inch (tpi): 12 2nd end Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Extend Size 1.062 inches 2nd end Strates Pressure: 1.062 inches 2nd end Matrimum Operating Pressure:	
Outside Diameter: 0.625 inches Minimum Inside Bending Radius: 5.500 inches End Application: Support equipment, c-17a and f-17 aircraft Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Features Provided: Nuts drilled for lockwire Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire. Maximum Operating Pressure: 1500.0 pounds per square inch Extres Thread Size: 1.062 inches 2nd end Seet Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Synouth Special Features:	
0.626 inches Minimum Inside Bending Radius: 5.00 inches End Application: Support equipment, c-17a and f-17 aircraft Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Features Provided: Nuts drilled for lockwire Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Special Features:	
Minimun Inside Bending Radius: 5:500 inches End Application: Support equipment, c-17a and f-17 aircraft Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Features Provided: Nuts drilled for lockwire Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1.062 inches 2nd end Steat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inread Size: 1.062 inches 2nd end Set Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inread Size: 1.062 inches 2nd end Set Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Synooth Special Features:	
5.500 inches End Application: Support equipment, c-17a and f-17 aircraft Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Features Provided: Nuts drilled for lockwire Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Note 3 partial Pressure: 1.062 inches 2nd end Straight 2nd end Burst Test Pressure: 1.062 inches 2nd end Straight 2nd end Straight 2nd end Burst Test Pressure: 1.062 inches 2nd end Straight 2nd end Straight 2nd end Straight 2nd end Burst Test Pressure: 1.062 inches 2nd end Straight 2nd end Straight 2nd end Straight 2nd end Straight 2nd end Burst Test Pressure: 1.062 inches 2nd end Straight 2nd end Burst Test Pressure: 1.062 inches 2nd end Straight 2nd end	
End Application: Support equipment, c-17a and f-17 aircraft Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Features Provided: Nuts drilled for lockwire Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Strieg Strieg	
Supor equipment, c-17a and f-17 aircraft Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Features Provided: Nuts drilled for lockwire Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Entread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smoth Special Features:	
Conection Style: Swivel nut flare 2nd end End Connection Design: Straight 2nd end Conection Type: Threaded internal tube 1st end Features Provided: Nuts drilled for lockwire Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch External Steel 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Special Features:	
Swivel nut flare 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Features Provided: Nuts drilled for lockwire Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Finde Surface Condition: Somoth Bread Size: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Somoth Bread Strip Eatures:	
End Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endFeatures Provided:Nuts drilled for lockwireThready Qty Per Inch (tpi):12 2nd endBurst Test Pressure:7000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchEntred Size:1.062 inches 2nd endSeat Angle:37.0 degrees 2nd endHydrostatic Test Pressure:3000.0 pounds per square inchInside Surface Condition:SomothSmoothSentaria Elemes:SomothSentaria Elemes:	-
Straight 2nd endConnection Type:Threaded internal tube 1st endFeatures Provided:Futures Provided:Nuts drilled for lockwireThready Qty Per Inch (tpi):12 2nd endBurst Test Pressure:7000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:1.062 inches 2nd endSet Angle:37.0 degrees 2nd endHydrostatic Test Pressure:3000.0 pounds per square inchInside Surface Condition:SmoothSmooth	
Conection Type: Threaded internal tube 1st end Features Provided: Nuts drilled for lockwire Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Smooth	
Threaded internal tube 1st end Features Provided: Nuts drilled for lockwire Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Smooth	-
Features Provided: Nuts drilled for lockwire Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Special Features:	
Nuts drilled for lockwire Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Special Features:	
Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Special Features:	
12 2nd end Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Special Features:	
Burst Test Pressure: 7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Special Features:	
7000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Special Features:	
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Special Features:	
Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Special Features:	
Maximum Operating Pressure:1500.0 pounds per square inchThread Size:1.062 inches 2nd endSeat Angle:37.0 degrees 2nd endHydrostatic Test Pressure:3000.0 pounds per square inchInside Surface Condition:SmoothSpecial Features:	
1500.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Special Features:	-
Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Special Features:	
1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Special Features:	
Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Special Features:	
37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Special Features:	
Hydrostatic Test Pressure: 3000.0 pounds per square inch Inside Surface Condition: Smooth Special Features:	
3000.0 pounds per square inch Inside Surface Condition: Smooth Special Features:	-
Inside Surface Condition: Smooth Special Features:	
Smooth Special Features:	
Special Features:	Inside Surface Condition:
	Smooth
Hose assembly has prebent angles	Special Features:
	Hose assembly has prebent angles

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0