NSN 4720-01-422-7222

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-422-7222

Cross Sectional Shape:				
Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.375 inches				
Tempurature Rating:				
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response				
Outside Diameter:				
0.690 inches				
Minimum Inside Bending Radius:				
2.500 inches				
Exterior Color:				
Black				
End Application:				
1740-01-253-8064; support equipment, c-17a aircraft				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Burst Test Pressure:				
16000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic				
Maximum Operating Pressure:				
4000.0 pounds per square inch				
Thread Size:				
0.750 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
8000.0 pounds per square inch				
Outer Covering Environmental Protection:				
Abrasion resistant and oil resistant and weatherproof				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				

15.750 inches

NSN 4720-01-422-7222

Nonmetallic Hose Assembly - Page 2 of 2



_	brood	Carias	Docionatori
ı	meau	oenes	Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0