Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-422-7846

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.500 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Black
End Application:
2330-01-378-9997
Connection Style:
Flared 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external tube 2nd end
Burst Test Pressure:
950.0 pounds per square inch
Layer Composition And Location:
1st layer braided fiber and outer layer molded plastic
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.500 inches 2nd end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure:
475.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
17.000 inches working
Thread Series Designator:
Nptf 2nd end
Shelf Life:
N/a

NSN 4720-01-422-7846

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0