NSN 4720-01-422-9551

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-422-9551

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 15.8 millimeters |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response |
| Outside Diameter: |
| 23.1 millimeters |
| Minimum Inside Bending Radius: |
| 5.000 inches |
| End Application: |
| 3930-01-384-5310 |
| Connection Style: |
| Swivel nut, gasket seal 2nd end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 14 2nd end |
| Burst Test Pressure: |
| 1400.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided textile yarn and outer layer spirally wrapped rubber fabric |
| Maximum Operating Pressure: |
| 350.0 pounds per square inch |
| Thread Size: |
| 1.000 inches 2nd end |
| Hydrostatic Test Pressure: |
| 700.0 pounds per square inch |
| Flow Angle: |
| 45.0 degrees 2nd end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 1498.6 millimeters working |
| Thread Series Designator: |

Uns 2nd end

NSN 4720-01-422-9551

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0