Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-422-9554

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.620 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response
Outside Diameter:
0.910 inches
Minimum Inside Bending Radius:
5.000 inches
End Application:
3930-01-384-5310
Connection Style:
Swivel nut, gasket seal 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
14 2nd end
Burst Test Pressure:
1400.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and outer layer spirally wrapped rubber fabric
Maximum Operating Pressure:
350.0 pounds per square inch
Thread Size:
1.000 inches 2nd end
Hydrostatic Test Pressure:
700.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
1397.0 millimeters working
Thread Series Designator:
Uns 2nd end

## NSN 4720-01-422-9554

Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0