NSN 4720-01-423-4415

Cross Sectional Shape:

Round

Thread Class: 2b 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-423-4415

Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.375 inches					
Tempurature Rating:					
-50.0 degrees fahrenheit and 212.0 degrees fahrenheit single response					
Outside Diameter:					
0.713 inches					
Minimum Inside Bending Radius:					
2.500 inches					
End Application:					
3930-01-298-5737					
Connection Style:					
Swivel nut, gasket seal 2nd end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Burst Test Pressure:					
12000.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided wire and outer layer braided polyester cord					
Maximum Operating Pressure:					
3000.0 pounds per square inch					
Thread Size:					
0.688 inches 2nd end					
Hydrostatic Test Pressure:					
6000.0 pounds per square inch					
Flow Angle:					
90.0 degrees 2nd end					
Outer Covering Environmental Protection:					
Abrasion resistant					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
79.330 inches working					
Media For Which Designed:					

Fuel/oil, hydrocarbon single response

NSN 4720-01-423-4415

Nonmetallic Hose Assembly - Page 2 of 2



	laa a al	C!	D!	_4
ı	nread	Series	Design	ator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0