NSN 4720-01-423-4910

Smooth

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-423-4910

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
1.210 inches
Minimum Inside Bending Radius:
7.380 inches
End Application:
2320-01-355-3062; used on weapon system truck, family of medium tactical vehicle (fmtv)
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
1500.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated fabric
Maximum Operating Pressure:
375.0 pounds per square inch
Thread Size:
1.312 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
750.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Vacuum In Torr:
381.0
Inside Surface Condition:

NSN 4720-01-423-4910

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
59.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Un 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0