Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-424-4024

Cross Sectional Sha	ine:
Round	
Inside Diameter:	
0.250 inches	
Tempurature Rating	
	• neit and 212.0 degrees fahrenheit single response
Outside Diameter:	
0.500 inches	
Minimum Inside Ben	nding Radius:
3.000 inches	j
Quick Disconnect Si	ize:
0.250 inches 1st end	
End Application:	
5820-01-387-6700	
Connection Style:	
Push (external) 1st er	nd
End Connection Des	sign:
Straight 1st end	
Connection Type:	
External quick discon	nect 1st end
Burst Test Pressure	:
1440.0 pounds per so	juare inch
Layer Composition	And Location:
1st layer braided texti	le yarn and outer layer molded rubber, synthetic
Maximum Operating	Pressure:
360.0 pounds per squ	lare inch
Hydrostatic Test Pre	essure:
720.0 pounds per squ	lare inch
Vacuum In Torr:	
50.8	
Inside Surface Cond	lition:
Smooth	
Measuring Method A	And Length:
72.000 inches	
Media For Which De	signed:
Fuel/oil, hydrocarbon	single response
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 4720-01-424-4024

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

