NSN 4720-01-424-4025

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-424-4025 **Cross Sectional Shape:** Round **Inside Diameter:** 0.312 inches **Tempurature Rating:** -55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.610 inches **Minimum Inside Bending Radius:** 2.750 inches **Quick Disconnect Size:** 0.312 inches 1st end **End Application:** 5820-01-387-6700 **Connection Style:** Push (internal) 1st end **End Connection Design:** Straight 1st end **Connection Type:** Internal quick disconnect 1st end **Burst Test Pressure:** 6000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric **Maximum Operating Pressure:** 1500.0 pounds per square inch **Hydrostatic Test Pressure:** 3000.0 pounds per square inch Vacuum In Torr: 50.8 **Inside Surface Condition: Measuring Method And Length:** 72.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 4720-01-424-4025

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0