NSN 4720-01-424-4026

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-424-4026

0.212 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.485 inches
Minimum Inside Bending Radius:
3.000 inches
End Application:
W/s code, aircraft, b-2 bomber
Connection Style:
Swivel nut, inverted flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
24 2nd end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
8.5 degrees 2nd end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
22.000 inches working

NSN 4720-01-424-4026

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unjs 2nd end
Specification Data:
1w025-07a287 manufacturers standard
Shelf Life:
N/a

Demilitarization:

Unit Of Measure:

No

Fiig:

A542a0