

View Online at <https://aerobasegroup.com/nsn/4720-01-424-9102>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 145.0 degrees fahrenheit single response

Outside Diameter:

1.250 inches

Minimum Inside Bending Radius:

5.000 inches

End Application:

Support equipment, b-1 aircraft

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thread Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

1200.0 pounds per square inch

Layer Composition And Location:

1st layer woven cotton with interwoven steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

300.0 pounds per square inch

Thread Size:

1.062 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

600.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Oil resistant and weatherproof and mildew resistant and salt water resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

52.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0