

View Online at <https://aerobasegroup.com/nsn/4720-01-424-9846>

Cross Sectional Shape:

Round

Inside Diameter:

4.000 inches

Tempurature Rating:

-68.0 degrees fahrenheit single response

Bolt Circle Diameter:

7.500 inches 2nd end

Flange Thickness:

0.938 inches 2nd end

Outside Diameter:

5.265 inches

Minimum Inside Bending Radius:

23.000 inches

Inner Conveying Tube Style:

Annular close-pitch corrugated

Bolt Hole Quantity:

8 2nd end

Flange Outside Diameter:

9.000 inches 2nd end

End Application:

Engine aircraft, f100-pw-100 (f-15a/b/c/d; 4920013901852

Connection Style:

Plain 2nd end

Bolt Hole Diameter:

0.750 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

600.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

150.0 pounds per square inch

Hydrostatic Test Pressure:

300.0 pounds per square inch

Measuring Method And Length:

20.250 inches

Flange Style:

Round w/ bolt holes 2nd end

Special Features:

Second end is a floating flange which moves or rotates

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0