

View Online at <https://aerobasegroup.com/nsn/4720-01-424-9846>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

4.000 inches

**Tempurature Rating:**

-68.0 degrees fahrenheit single response

**Bolt Circle Diameter:**

7.500 inches 2nd end

**Flange Thickness:**

0.938 inches 2nd end

**Outside Diameter:**

5.265 inches

**Minimum Inside Bending Radius:**

23.000 inches

**Inner Conveying Tube Style:**

Annular close-pitch corrugated

**Bolt Hole Quantity:**

8 2nd end

**Flange Outside Diameter:**

9.000 inches 2nd end

**End Application:**

Engine aircraft, f100-pw-100 (f-15a/b/c/d; 4920013901852

**Connection Style:**

Plain 2nd end

**Bolt Hole Diameter:**

0.750 inches 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Plain face flange 2nd end

**Burst Test Pressure:**

600.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

150.0 pounds per square inch

**Hydrostatic Test Pressure:**

300.0 pounds per square inch

**Measuring Method And Length:**

20.250 inches

**Flange Style:**

Round w/ bolt holes 2nd end

**Special Features:**

Second end is a floating flange which moves or rotates

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0