NSN 4720-01-424-9848

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-424-9848

| view Offilite at https://aerobasegroup.com/hish/4720-01-424-3040 |
|--|
| Cross Sectional Shape: |
| Round |
| Inside Diameter: |
| 1.000 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Flange Thickness: |
| 0.315 inches 1st end |
| Outside Diameter: |
| 1.500 inches |
| Minimum Inside Bending Radius: |
| 12.000 inches |
| Angle Between Rigid Elbow Fittings In Deg: |
| 0.0 |
| Flange Outside Diameter: |
| 1.750 inches 1st end |
| End Application: |
| Support equipment, b-1 aircraft |
| Connection Style: |
| Plain 1st end |
| End Flange Construction: |
| Solid 1st end |
| End Connection Design: |
| Elbow 1st end |
| Connection Type: |
| Plain face flange 1st end |
| Burst Test Pressure: |
| 14000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 3500.0 pounds per square inch |
| Hydrostatic Test Pressure: |
| 7000.0 pounds per square inch |
| Flow Angle: |
| 90.0 degrees 1st end |
| Outer Covering Environmental Protection: |
| Oil resistant and weatherproof |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |

85.000 inches

NSN 4720-01-424-9848

Nonmetallic Hose Assembly - Page 2 of 2



| Flange Style | Fla | ang | e : | Sty | Ιle | : |
|--------------|-----|-----|-----|-----|-----|---|
|--------------|-----|-----|-----|-----|-----|---|

Round w/ out bolt holes 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0