

View Online at <https://aerobasegroup.com/nsn/4720-01-424-9849>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.625 inches

Temperature Rating:

-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

1.078 inches

Minimum Inside Bending Radius:

2.750 inches

End Application:

W/s code, support equipment, b-1 aircraft

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

3000.0 pounds per square inch

Layer Composition And Location:

1st layer braided polyester cord and 2nd layer braided wire and outer layer braided textile yarn

Maximum Operating Pressure:

750.0 pounds per square inch

Thread Size:

1.062 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

1500.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

12.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0