

View Online at <https://aerobasegroup.com/nsn/4720-01-425-2113>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Outside Diameter:

0.620 inches

Minimum Inside Bending Radius:

2.500 inches

Exterior Color:

Black

End Application:

4940-01-385-1794; support equipment, c-17a aircraft

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and outer layer molded rubber, nitrile

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and abrasion resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

38.000 inches

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0