NSN 4720-01-426-2445

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-426-2445 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.406 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.760 inches **Minimum Inside Bending Radius:** 1.750 inches **End Application:** ARMO-RE-DCO-MBAT **Connection Style:** Swivel, plain 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded external tube 1st end Thready Qty Per Inch (tpi): 16 1st end **Burst Test Pressure:** 4000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and 2nd layer braided steel wire and outer layer rubber impregnated braided fabric **Maximum Operating Pressure:** 1000.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

24.000 inches and 25.000 inches

NSN 4720-01-426-2445

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0