NSN 4720-01-426-5013

Cross Sectional Shape:

Inside Diameter: 3.050 inches

Tempurature Rating:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-426-5013

410.0 degrees fahrenheit single response
Bolt Circle Diameter:
5.500 inches 1st end
Flange Thickness:
0.500 inches 1st end
Outside Diameter:
3.500 inches
Minimum Inside Bending Radius:
15.000 inches
Bolt Hole Quantity:
8 1st end
Flange Outside Diameter:
6.625 inches 1st end
End Application:
An/spy-1a fwd/suct; arleigh burke class ddg
Connection Style:
Plain 1st end
Bolt Hole Diameter:
0.562 inches 1st end
End Flange Construction:
Solid 1st end
Fuel Commention Product
End Connection Design:
Straight 1st end
-
Straight 1st end
Straight 1st end Connection Type:
Straight 1st end Connection Type: Plain face flange 1st end
Straight 1st end Connection Type: Plain face flange 1st end Burst Test Pressure:
Straight 1st end Connection Type: Plain face flange 1st end Burst Test Pressure: 800.0 pounds per square inch
Straight 1st end Connection Type: Plain face flange 1st end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location:
Straight 1st end Connection Type: Plain face flange 1st end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire
Straight 1st end Connection Type: Plain face flange 1st end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:
Straight 1st end Connection Type: Plain face flange 1st end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch
Straight 1st end Connection Type: Plain face flange 1st end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Hydrostatic Test Pressure:
Straight 1st end Connection Type: Plain face flange 1st end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch
Straight 1st end Connection Type: Plain face flange 1st end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Inside Surface Condition:
Straight 1st end Connection Type: Plain face flange 1st end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Inside Surface Condition: Convoluted

NSN 4720-01-426-5013

Fiig: A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Flange Style:
Round w/ bolt holes 1st end
Special Features:
Two hose assemblies connected by 90 degrees elbow, first leg length 37.000 in., second leg length 36.000 in.
Reference Number Differentiating Characteristics:
As differentiated by special features
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No