Nonmetallic Hose Assembly - Page 1 of 2



layer spirally laid corrosion resistant steel wire

View Online at https://aerobasegroup.com/nsn/4720-01-428-3275

view Online at https://aciobasegioup.com/nsi//4/20-01-420-02/0
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.219 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.440 inches
Minimum Inside Bending Radius:
2.000 inches
End Application:
File set, helicopter, bell helicopter textron inc
Connection Style:
Swivel nut with compression sleeve 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
1st layer rubber impregnated braided corrosion resistant steel wire and outer
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
19.000 inches
Special Test Features:
Hose cert to faa tso-c53a type a
Thread Series Designator:
Unjf 1st end

## NSN 4720-01-428-3275

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

