NSN 4720-01-428-6808

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-428-6808

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.343 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
17.500 inches
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a

NSN 4720-01-428-6808

Nonmetallic Hose Assembly - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A542a0