

View Online at <https://aerobasegroup.com/nsn/4720-01-429-9897>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-50.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

0.781 inches

First End Fitting Specification/std Data:

Saej516, 6-6 3001xx standard (includes industry or association standards, individual manufactureer standards, etc.).

Second End Fitting Specification/std Data:

Saej516, 6-6 3014xx standard (includes industry or association standards, individual manufactureer standards, etc.).

End Application:

Truck, family of medium tactical vehicle {fmtv}

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Fitting Component And Surface Treatment:

Complete fitting zinc all ends

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

900.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic err-100

Maximum Operating Pressure:

150.0 pounds per square inch

Thread Size:

0.625 inches 1st end

Seat Angle:

45.0 degrees 2nd end

Hydrostatic Test Pressure:

300.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

1257.9 millimeters

Second End Swivel Action Capability:

Not included

Media For Which Designed:

Air single response

Thread Series Designator:

Unf 2nd end

Specification Data:

Saej516, 6-6 3001xx national std/spec and saej516, 6-6 3014xx national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0