## NSN 4720-01-430-0247

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-430-0247

Cross Sectional Shape:  Round  Thread Direction:  Right-hand 1st end  Inside Diameter:  0.250 inches  Tempurature Rating:
Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating:
Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating:
Inside Diameter:  0.250 inches  Tempurature Rating:
0.250 inches  Tempurature Rating:
Tempurature Rating:
45.0 degrees fabranhait single response and 500.0 degrees fabranhait single response
-45.0 degrees fahrenheit single response and 500.0 degrees fahrenheit single response
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut, flareless 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
10000.0 pounds per square inch
Maximum Operating Pressure:
1500.0 pounds per square inch
Seat Angle:
12.0 degrees 1st end
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
21.000 inches
Test Data Document:
81349-mil-h-25579 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A542a0
Mil-std (military Standard):

Mil-h-25579 spec.