NSN 4720-01-430-2725

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-430-2725

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.407 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.715 inches
Minimum Inside Bending Radius:
5.750 inches
Hose Or Tubing Specification/std Data:
Sae as604, size 8-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).
First End Fitting Specification/std Data:
Nas 1760-08 standard (includes industry or association standards, individual manufactureer standards, etc.).
End Application:
Aircraft, hercules c-130
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
10500.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire err-100
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.750 inches 1st end

12.0 degrees 1st end

Seat Angle:

NSN 4720-01-430-2725

Nonmetallic Hose Assembly - Page 2 of 2



Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
42.000 inches working
Special Features:
Inner conveying tube material-plastic, tetrafluoroethylene
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0