Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-430-3847

	al Shape:
Round	
Thread Class:	
3b 1st end	
Thread Directi	
Right-hand 1st	
Inside Diamete	۶r:
1.375 inches	
Tempurature F	
	ahrenheit and 160.0 degrees fahrenheit single response
Outside Diame	iter:
1.781 inches	
Minimum Insid	le Bending Radius:
11.000 inches	
End Application	n:
Aircraft, hercul	es c-130
Connection St	yle:
Swivel nut, flar	eless 1st end
End Connection	on Design:
Straight 1st end	I
Connection Ty	pe:
Threaded intern	nal tube 1st end
Thready Qty P	er Inch (tpi):
12 1st end	
Burst Test Pre	ssure:
2000.0 pounds	per square inch
Layer Compos	ition And Location:
1st layer braide	d cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord
Maximum Ope	rating Pressure:
500.0 pounds p	er square inch
Thread Size:	
1.875 inches 1	st end
Seat Angle:	
12.0 degrees 1	st end
Hydrostatic Te	st Pressure:
1000.0 pounds	per square inch
Inside Surface	Condition:
Smooth	
Measuring Me	thod And Length:
9.250 inches w	orking
Media For Whi	ch Designed:
Evel/eil budre	carbon single response

Nonmetallic Hose Assembly - Page 2 of 2



**Thread Series Designator:** 

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0