Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-431-1344

view Online at https://aerobasegroup.com/hsr/4720-01-451-154	4
Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.375 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single re	esponse
Outside Diameter:	
0.690 inches	
Minimum Inside Bending Radius:	
3.000 inches	
End Application:	
Shipboard material handling eqipment mhe)	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
1000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided cotton cord and outer layer molded rubber, but	ina-n
Maximum Operating Pressure:	
250.0 pounds per square inch	
Thread Size:	
0.562 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
500.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
14.500 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Unf 1st end	

## NSN 4720-01-431-1344

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

