## NSN 4720-01-433-3033



Nonmetallic Hose Assembly - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4720-01-433-3033
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
Between 0.304 inches and 0.343 inches
Minimum Inside Bending Radius:
2.000 inches
Angle Between Rigid Elbow Fittings In Deg:
0.0
End Application:
2815-01-414-6821; recovery vehicle fu
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
7000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire

#### **Maximum Operating Pressure:**

1500.0 pounds per square inch

#### **Thread Size:**

0.438 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

### **Hydrostatic Test Pressure:**

3000.0 pounds per square inch

### Flow Angle:

90.0 degrees 1st end

### **Inside Surface Condition:**

Smooth

### **Measuring Method And Length:**

6.000 inches working

# NSN 4720-01-433-3033

Nonmetallic Hose Assembly - Page 2 of 2



	•		
I hread	Series	Designator:	

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0