Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-433-7178

(Cross Sectional Shape:
F	Round
٦	Fhread Class:
3	3b 1st end
٦	Thread Direction:
F	Right-hand 1st end
I	nside Diameter:
(0.188 inches
٦	Tempurature Rating:
-	65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
(Dutside Diameter:
(0.312 inches
ľ	Minimum Inside Bending Radius:
2	2.000 inches
E	End Application:
2	2815-01-414-6821; used on the recovery vehicle fu
(Connection Style:
S	Swivel nut flare 2nd end
E	End Connection Design:
S	Straight 1st end
(Connection Type:
٦	Threaded internal tube 1st end
E	Burst Test Pressure:
1	2000.0 pounds per square inch
L	ayer Composition And Location:
(Duter layer braided corrosion resistant steel wire
	Maximum Operating Pressure:
1	500.0 pounds per square inch
٦	Thread Size:
(0.438 inches 1st end
ç	Seat Angle:
3	37.0 degrees 2nd end
ł	Hydrostatic Test Pressure:
3	3000.0 pounds per square inch
F	Flow Angle:
ć	00.0 degrees 2nd end
١	/acuum In Torr:
Ę	50.8
I	nside Surface Condition:
ŝ	Smooth
	Measuring Method And Length:
ç	67.500 inches

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0