Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-433-8259

····· ································
Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.585 inches
Minimum Inside Bending Radius:
4.620 inches
End Application:
2815-01-414-6821: w/s code recovery vehicle fu
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and oil resistant and alcohol resistant and solvent resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
40.000 inches working
Thread Series Designator:
Unf 1st end



**Specification Data:** 

96906-ms8005 government standard

## Specification Or Standard:

8 size and a style

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A542a0