

View Online at <https://aerobasegroup.com/nsn/4720-01-433-8262>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.406 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

**Outside Diameter:**

0.585 inches

**Minimum Inside Bending Radius:**

4.620 inches

**End Application:**

W/SC-OD-ERE-COVE

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

6000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fuel resistant and oil resistant and alcohol resistant and solvent resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

24.000 inches working

**Special Features:**

Hose od does not include the chafe guard

**Thread Series Designator:**

Unf 1st end

**Specification Data:**

96906-ms8005 government standard

**Specification Or Standard:**

8 size and a style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0