NSN 4720-01-435-2906

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-435-2906

Cross Sectional Shape:

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.585 inches
Minimum Inside Bending Radius:
4.620 inches
End Application:
Spruance class dd (963)
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nuts drilled for lockwire
Burst Test Pressure:
6000.0 pounds per square inch
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
13.000 inches working
Thread Series Designator:
Unjf 1st end
Shelf Life:

N/a

NSN 4720-01-435-2906

Nonmetallic Hose Assembly - Page 2 of 2



	• -			
In	ıŧ	()t	Measure	•

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-27267 spec.