NSN 4720-01-435-6036

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-435-6036

Thread Class:			
3b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
1.125 inches			
Tempurature Rating:			
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response			
Outside Diameter:			
1.400 inches			
Minimum Inside Bending Radius:			
11.000 inches			
End Application:			
Used on the nimitz class cvn			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Thready Qty Per Inch (tpi):			
12 1st end			
Burst Test Pressure:			
4000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
1000.0 pounds per square inch			
Thread Size:			
1.625 inches 1st end			
Seat Angle:			
37.0 degrees 1st end			
Hydrostatic Test Pressure:			
2000.0 pounds per square inch			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
27.960 inches			
Thread Series Designator:			
Unj 1st end			

NSN 4720-01-435-6036

Nonmetallic Hose Assembly - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0