Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-435-6366

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.250 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single	response
Outside Diameter:	·
0.375 inches	
Minimum Inside Bending Radius:	
3.000 inches	
End Application:	
Firetruck, p-19	
Connection Style:	
Plain optional end 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal pipe 2nd end	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.250 inches 2nd end	
Hydrostatic Test Pressure:	
6000.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
28.000 inches working	
Thread Series Designator:	
Npt 2nd end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 4720-01-435-6366

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

