## NSN 4720-01-435-9507

Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-01-435-9507 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.880 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 1.240 inches **Minimum Inside Bending Radius:** 3.500 inches Angle Between Rigid Elbow Fittings In Deg: 270.0 **End Application:** 2320-01-344-9887 **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Elbow 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 1600.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyester cord and 2nd layer braided wire and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 400.0 pounds per square inch **Thread Size:** 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 800.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

## NSN 4720-01-435-9507

Nonmetallic Hose Assembly - Page 2 of 2



| Inside Surface Condition:   |
|-----------------------------|
| Smooth                      |
| Measuring Method And Length |
| 43.375 inches working       |
| Thread Series Designator:   |
| Un 1st end                  |
| Shelf Life:                 |
| N/a                         |
| Unit Of Measure:            |
|                             |
| Demilitarization:           |
| No                          |

**Fiig:** A542a0