

View Online at <https://aerobasegroup.com/nsn/4720-01-436-0317>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.000 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

Flange Thickness:

0.312 inches 2nd end

Outside Diameter:

1.500 inches

Minimum Inside Bending Radius:

6.000 inches

Exterior Color:

Black

Center To Center Distance Between Bolt Holes Along Width:

1.030 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.062 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.780 inches 2nd end

End Application:

Iwo jima class lph

Flange Width:

2.220 inches 2nd end

Connection Style:

Plain w/ gasket groove (sae flanged head) 2nd end

Bolt Hole Diameter:

0.406 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

16000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, chloroprene err-100

Maximum Operating Pressure:

4000.0 pounds per square inch

Thread Size:

1.312 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

8000.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

110.000 inches working

Second End Swivel Action Capability:

Not included

Flange Style:

Double oval (sae split type flange) 2nd end

Special Features:

Inner conveying tube material-rubber, chloroprene

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0