Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-436-3488

| New Online at https://aerobasegroup.com/nsn/+/20-01-+00-0+00                          |
|---|
| Cross Sectional Shape:  |
| Round   |
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.312 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.469 inches  |
| Connection Style:   |
| Swivel nut, flareless 1st end   |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 90000.0 pounds per square inch  |
| Layer Composition And Location:   |
| Outer layer braided corrosion resistant steel wire                                    |
| Maximum Operating Pressure:   |
| 1500.0 pounds per square inch   |
| Thread Size:  |
| 0.562 inches 1st end  |
| Seat Angle:   |
| 12.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 3000.0 pounds per square inch   |
| Outer Covering Environmental Protection:  |
| Corrosion resistant   |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 28.000 inches   |
| Thread Series Designator:   |
| Unf 1st end   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |

---

## NSN 4720-01-436-3488

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

