

View Online at <https://aerobasegroup.com/nsn/4720-01-437-8803>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.500 inches

**Temperature Rating:**

-50.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response

**Outside Diameter:**

0.840 inches

**Minimum Inside Bending Radius:**

3.500 inches

**End Application:**

Used on weapon system truck, family of medium tactical vehicle (fmtv)-medium

**Connection Style:**

Swivel nut, gasket seal 2nd end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting zinc 1st end

**Connection Type:**

Threaded internal tube 1st end

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

12000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer braided steel wire err-100

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.812 inches 2nd end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Flow Angle:**

45.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

19.000 inches

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0