NSN 4720-01-438-3783

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-438-3783

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.630 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.938 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external hose 1st end
Features Provided:
Perforated outer cover
Burst Test Pressure:
1400.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operating Pressure:
35.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Hydrostatic Test Pressure:
700.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
81.000 inches
Special Features:
P19 convers k
Media For Which Designed:
Fuel/oil, hydrocarbon and hydraulic fluid, water base single response
Thread Series Designator:

Npt 1st end

NSN 4720-01-438-3783

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0