## NSN 4720-01-438-4904

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-438-4904

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 3b 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.500 inches   |
| Tempurature Rating:  |
| -50.0 degrees fahrenheit and 212.0 degrees fahrenheit single response                |
| Outside Diameter:  |
| 0.840 inches   |
| Minimum Inside Bending Radius:   |
| 3.500 inches   |
| End Application:   |
| 2320-01-354-4528; used on the truck, family of medium tactical vehicle (fmtv)-medium |
| Connection Style:  |
| Swivel nut, gasket seal 1st end  |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Burst Test Pressure:   |
| 12000.0 pounds per square inch   |
| Layer Composition And Location:  |
| 1st layer braided steel wire and outer layer molded plastic                          |
| Maximum Operating Pressure:  |
| 3000.0 pounds per square inch  |
| Thread Size:   |
| 0.812 inches 1st end   |
| Hydrostatic Test Pressure:   |
| 6000.0 pounds per square inch  |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 76.000 inches  |
| Media For Which Designed:  |
| Fuel/oil, hydrocarbon single response  |
| Thread Series Designator:  |
| Unjf 1st end   |
| Shelf Life:  |
| N/a  |

## NSN 4720-01-438-4904

Nonmetallic Hose Assembly - Page 2 of 2



|  | Of |  |  |  |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A542a0