## NSN 4720-01-438-6023



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-438-6023 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response **Outside Diameter:** 0.600 inches **Minimum Inside Bending Radius:** 4.000 inches **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 20000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 5000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 12.500 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response

Unf 1st end

**Thread Series Designator:** 

Shelf Life:

N/a

## NSN 4720-01-438-6023

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0