## NSN 4720-01-439-5003

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-439-5003

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-50.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.840 inches
Minimum Inside Bending Radius:
3.500 inches
End Application:
W/s code computer balistic, mortar m-23
Connection Style:
Swivel nut, gasket seal 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
16 2nd end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and outer layer molded plastic
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.812 inches 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
14.000 inches working
Media For Which Designed:

Fuel/oil, hydrocarbon single response

## NSN 4720-01-439-5003

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator	tor:
--------------------------	------

Un 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0