NSN 4720-01-439-5263

Cross Sectional Shape:

Round

Thread Class: 2b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-439-5263

Inside Diameter:
0.260 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
Outside Diameter:
0.570 inches
Minimum Inside Bending Radius:
3.000 inches
End Application:
2320-01-344-9887
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
20000.0 pounds per square inch
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
10000.0 pounds per square inch
10000.0 pounds per square inch Flow Angle:
Flow Angle:
Flow Angle: 45.0 degrees 1st end
Flow Angle: 45.0 degrees 1st end Outer Covering Environmental Protection:
Flow Angle: 45.0 degrees 1st end Outer Covering Environmental Protection: Fire resistant
Flow Angle: 45.0 degrees 1st end Outer Covering Environmental Protection: Fire resistant Inside Surface Condition:
Flow Angle: 45.0 degrees 1st end Outer Covering Environmental Protection: Fire resistant Inside Surface Condition: Smooth
Flow Angle: 45.0 degrees 1st end Outer Covering Environmental Protection: Fire resistant Inside Surface Condition: Smooth Measuring Method And Length:

NSN 4720-01-439-5263

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0